



Scan Barcode and UHF Rain RFID with iPhone®, iPad® and iPod touch®

Long Range



FC CE



Easy Connect

Whenever you need it, place your Smart Device on it and go!

32 feet (10m) away

Read UHF RFID tags more than 32 feet (10m) away
* it may depend on the tags.

Support various Devices

Compatible with most devices including iPhones, iPads, Android phones, tablets, and more.

< Body + Parts >



AsReader (ASR-R250G) Product Data

| Model Name | | ASR-R250G | |
|-----------------------|---|---|---|
| RFID | Spec | ISO 18000-63 (Formerly known as: ISO 18000-6 Type C) / EPC Class1 Gen2 | |
| | Bandwidth | 902 - 928Mhz / 865 - 868Mhz | |
| | Output power | 1W (30dBm) | |
| | Reading distance | 0 to 32 ft. (0 to 10m) or more *1 | |
| | Polarization characteristics | Linear | |
| Function | | Read / Write / Lock / Delete | |
| Barcode (Optional) *2 | Scan Engine | CMOS Sensor | |
| | Reading range | Barcode density | Distance from scanner |
| | | 100% U.P.C. | 46 - 419 mm (1.8 - 16.5") |
| | | 5 mil Code 39 | 64 - 163 mm (2.5 - 6.5") |
| | | 10 mil Code 39 | 28 - 338 mm (1.1 - 13.3") |
| | | 6.7 mil PDF417 | 46 - 185 mm (1.8 - 7.3") |
| | 10 mil Data Matrix | 53 - 203 mm (2.1 - 8.0") | |
| Reading width | 42.4° (horizontal), 33° (vertical) | | |
| Reading angle | Pitch: ±45° Roll: 360° Skew motion: ±60° *3 | | |
| Reading code | • 1D: UPC/EAN/JAN, GS1 DataBar, Code 39, Code 128, Code 32, Code 93, Codabar/NW7, Interleaved 2 of 5, Code 2 of 5, Matrix 2 of 5, MSI, Telepen, Trioptic, China Post • 2D Stacked: PDF417, MicroPDF417, GS1 Composite • 2D Matrix: Aztec Code, Data Matrix, QR Code, Micro QR Code, MaxiCode, Han Xin Code • Postal: Intelligent Mail Barcode, Postal-4i, Australian Post, British Post, Canadian Post, Japanese Post, Netherlands (KIX) Post, Postnet, Planet Code • OCR Option: OCR-A, OCR-B, E13B (MICR) | | |
| Light sources | Illumination: White LED, Aiming: Red Laser (Class 2) | | |
| Power Source | Battery Capacity | Rechargeable lithium-ion battery 2600mAh | |
| | Continuous operation time | • Barcode Every 10sec: about 17 hours (about 6,000 times) Every 5 sec: about 13 hours (about 9,000 times) | • RFID 5 Sec Reading 30 Sec Waiting: about 9 hours (about 900 times) 10 Sec Reading 30 Sec Waiting: about 5 hours (about 400 times) |
| | Power Source | Magconn *4, MicroUSB | |
| | Charging time | About 4 hours (Built-in battery) *5 | |
| Key input | | Trigger, Mode, Power, Reset | |
| Communication | Interface | USB | |
| Appearance | Dimensions (W) x (D) x (H) | 1.75" x 6.89" x 6.04" (48.0 x 174.95 x 153.5mm) | |
| | Weight (with Battery) | 11.2 oz (320g) | |
| | Material | PC | |
| | Casing color | White/Gray | |
| | LED | Switch ON (Blue) /Reading (Blue blinking) /Charging (Red) /Charge complete (Red blinking to no light) | |
| Environment | Operating environment | 32° ~ 95° F (0° ~ 35° C) | |
| | Charge environment | 32° ~ 113° F (0° ~ 45° C) | |
| | Storage environment | -4° ~ 140° F (-20° ~ 60° C) | |
| | IP Rating | IP54 compliance | |
| | Anti-drop | (All 6-sides, twice each) 4 ft. (1.5m) *6 | |
| Certificates | | TELEC/FCC/CE/PSE (battery) | |
| Bundled items | | microUSB cable Manual | |

*1 This may depend on the tag or enviroment.

*2 The Barcode scanner module is optional.

*3 This may depend on the barcode type.

*4 An AC adapter with an ouptput of 5V 2A is strongly recommended for the Magconn cable.

*5 The battery in the reader is charged first and then the connected smart device is charged next.

*6 Reader only. Not including smartphone



For more information:

web: <http://www.spartag-id.com>

email: sales@spartag-id.com



SAS SparTag
 21 place de l'union européenne
 91300 MASSY
 Tel : +33(0)9 80 75 06 05

AsReader, Inc.

tel +1 (949)438-7577
 fax +1 (949) 438-7570
 14451 Chambers Road, Suite 2150
 Tustin, CA 92780-6976 USA